



AREAS OF APPLICATION

- Warehouses and logistic halls
- Production facilities
- Exhibition & showrooms

PRODUCT BENEFITS

- Durable die-cast aluminium housing with akzonobel stoving varnish finish and corrosion-resistant body.
- Low maintenance and operation costs due to long lifetime of LED
- High performance design and Efficacy up to 120LM/W
- High efficiency and reliability
- Massive aluminum die-cast heat sink with notably good heat dissipation abilities

PRODUCT FEATURES

- Durable and compact low-profile housing design
- IP65 for indoor and outdoor applications
- 3 Years warranty

TECHNICAL DATA

Electrical data

Rated power	208W
Operating voltage	AC 100-305V
Operating frequency	50/60Hz.
Power factor	>0.9

Photometrical data

Color temperature	2700-6500K.
Luminous flux	24960LM.
Color rendering index Ra	80

Light Technical Data

Beam angle	AC 100-305V
------------	-------------

Dimensions

Inner Diameter	Ø450mm.
Height	114mm.

Temperature & operating conditions

Ambient Temperature	-25°C ~50°C
---------------------	-------------

General information

Mounting type	Suspended
LED type	SMD LED
Lifespan	30,000h.



SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
CLX 0180U-200	120±10 lm/W	208W	65	NO

TECHNICAL DRAWING

