






AREAS OF APPLICATION

-  Landscape Area
-  Outdoor Pathway
-  Garden

PRODUCT BENEFITS

-  Matching colour temperature and finish to the Architectural exterior range.
-  Die-cast aluminium construction with Stainless steel front and Clear toughened glass
-  Good glare reduction and Low maintenance and operation costs
-  Suitable for use in areas with Garden and Outdoor Pathway
-  Excellent diffused beam shape from a range of optics

PRODUCT FEATURES

-  Type of protection: IP66
-  2 Years Warranty.
-  Colour Rendering Index R:80

TECHNICAL DATA

Electrical data

Rated power	30W
Operating voltage	AC100-240V
Operating frequency	50/60Hz
Power factor	0.90

Photometrical data

Color temperature	2700-6500K
Luminous flux	2100lm
Color rendering index Ra	80

Light Technical Data

Beam angle	45°, 60°, 15×30°
------------	------------------

Dimensions

Inner Diameter	Ø165mm
Height	567

Temperature & operating conditions

Ambient Temperature	-25°...+50°C
---------------------	--------------

General information

Mounting type	Spike mounting
LED type	CREE COB LED
Lifespan	50,000h



SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
CLX1103SB-18	70	30W	66	NO

TECHNICAL DRAWING

