










AREAS OF APPLICATION

-  Landscape Area
-  Outdoor Pathway
-  Garden

PRODUCT BENEFITS

-  Highly efficient COB LED chip and high IP rating on luminaire front side.
-  Die-cast aluminum housing with Clear tempered Glass + SS316L
-  Good glare reduction and Low maintenance and operation costs
-  High quality lens made of polycarbonate, secondary optics with tempered glass cover
-  Excellent diffused beam shape from a range of optics

PRODUCT FEATURES

-  Type of protection: IP67
-  High Quality CREE LED Chip
-  Colour Rendering Index R:80

TECHNICAL DATA

Electrical data

Rated power	16W
Operating voltage	AC100-240V
Operating frequency	50/60Hz
Power factor	0.90

Photometrical data

Color temperature	2700-6500K
Luminous flux	1200lm
Color rendering index Ra	80

Light Technical Data

Beam angle	30°,45°
------------	---------

Dimensions

Inner Diameter	Ø143mm
Height	160

Temperature & operating conditions

Ambient Temperature	-25~+ 50°C
---------------------	------------

General information

Mounting type	Recessed
LED type	CREE LED
Lifespan	50,000h



SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
CLX 2110CC-7	75lm/W	16W	67	NO

TECHNICAL DRAWING

