














AREAS OF APPLICATION

-  General indoor illumination
-  Decorative lighting ,Corridors
-  Facade accent lighting

PRODUCT BENEFITS

-  Highest quality components and premium packaged 2835 LEDs
-  Easy mounting on many smooth surfaces thanks to self-adhesive tape at the back
-  High-performance silicone for extremely long life and flexibility
-  Direct connection to AC power supply thanks to integrated control gear
-  Three Row Dimmable led strip with Push-in connectors enable automatic wiring

PRODUCT FEATURES

-  Type of protection: IP65
-  Material:Polycarbonate
-  Type of LED:SMD 2835,276LED/m

TECHNICAL DATA

Electrical data

Rated power	24W/m
Operating voltage	AC 220V
Operating frequency	50/60Hz
Power factor	0.90

Photometrical data

Color temperature	2700-6500K
Luminous flux	22lm/LED
Color rendering index Ra	>80

Light Technical Data

Beam angle	120°
------------	------

Dimensions

Length	50000mm
Width	15mm

Temperature & operating conditions

Ambient Temperature	-15°~ +60°
---------------------	------------

General information

Colour consistency	≤ 3 SDCM
LED type	LED SMD
Lifespan	35,000h



SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
2835-276P-15	22lm/LED	24W/m	65	NO

TECHNICAL DRAWING

