








AREAS OF APPLICATION

-  Landscape Area
-  Wallwashing of building facades
-  General Outdoor Lighting

PRODUCT BENEFITS

-  Even, brilliant lighting effects due to extra narrow, asymmetric or wide optics
-  Simple and Constant current driver with PWM gray control installed inside.
-  Prewired plug connector (male/female) for easy installation
-  High quality lens made of polycarbonate, secondary optics with tempered glass cover

PRODUCT FEATURES

-  Type of protection: IP65
-  3 Years Warranty.
-  Colour rendering index Ra: ≥ 80

TECHNICAL DATA

Electrical data

Rated power	10W
Operating voltage	DC24V
Operating frequency	-
Power factor	0.90

Photometrical data

Color temperature	2700-6500K
Luminous flux	650lm
Color rendering index Ra	-

Light Technical Data

Beam angle	120°
------------	------

Dimensions

Length	1000mm
Width	49mm

Temperature & operating conditions

Ambient Temperature	-25~+ 50° C
---------------------	-------------

General information

Mounting type	Surface
LED type	CREE LED
Lifespan	30,000h



SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE/CONTROL
CLX 3317L-48	65lm/W	10W	66	RGBW

TECHNICAL DRAWING

