














## AREAS OF APPLICATION

-  General illumination
-  Halls, offices, conference rooms
-  Retail and Shopping mall

## PRODUCT BENEFITS

-  Affordable solution for retrofit or new installations
-  Exceptionally stable CRI across all colour temperature
-  Die-cast aluminum housing for improved heat dissipation
-  Suitable for use in areas with low ceilings thanks to compact design
-  Excellent diffused beam shape from a range of optics

## PRODUCT FEATURES

-  Type of protection: IP20
-  Cutout diameter: Ø200mm
-  Colour Rendering Index R:80

## TECHNICAL DATA

### Electrical data

Rated power	30W
Operating voltage	AC190-265V
Operating frequency	50/60Hz
Power factor	0.90

### Photometrical data

Color temperature	2700-6500K
Luminous flux	3000lm
Color rendering index Ra	80

### Light Technical Data

Beam angle	120°
------------	------

### Dimensions

Outer diameter	Ø220mm
Height	80mm

### Temperature & operating conditions

Ambient Temperature	-15° ~ +50°
---------------------	-------------

### General information

Mounting type	Ceiling Recessed
LED type	COB LED
Lifespan	50,000h



SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
CLX8-55511	100lm/W	30W	20	NO

**TECHNICAL DRAWING**

