



AREAS OF APPLICATION

- Garages and parking lots
- Entrance areas and walkways
- Storage areas

PRODUCT BENEFITS

- It has a unique round shape made of die-cast aluminium heatsink with a perfect performance for the application.
- These low profile fixtures feature a highly reliable LED light engine and an impact resistant polycarbonate optical diffuser.
- This lamp has a built-in sensor to activate the light only in the right time when it is really needed.

PRODUCT FEATURES

- High efficiency up to 130lm/w
- IP65 Grade protection
- Wide 150° degree light distribution
- Low glare, precisely designed optical PC lens
- Quick to install and easy to use, secure
- 5 Years warranty
- Energy efficiency class A+

TECHNICAL DATA

Electrical data

Rated power	60 W
Operating voltage	AC100~277V
Operating frequency	47~63Hz
Power factor	>0.9

Photometrical data

Color temperature	2700K - 6500K
Luminous flux (lm)	7800 ± 600
Color rendering index Ra	>80

Light Technical Data

Beam angle	150°
------------	------

Dimensions

Height (mm)	121.5
Diameter (mm)	285.0

Temperature & operating conditions

Ambient Temperature	-30~+50°C
---------------------	-----------

General information

Mounting type	Surface mounted
LED type	SMD LED
Lifespan	50000 hours

SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
CLX CP-60W	130 ±10lm/W	60 W	65	YES

TECHNICAL DRAWING

