












## AREAS OF APPLICATION

-  Warehouses
-  Logistic halls
-  Production facilities

## PRODUCT BENEFITS

-  Unique heat sink design with air channels to increase system reliability
-  Low maintenance and operation costs due to long lifetime of LED
-  High efficiency and reliability
-  Massive aluminium die - cast heat sink with notably good heat dissipation abilities
-  High performance design and efficacy upto 140 lm/W

## PRODUCT FEATURES

-  Durable and compact low-profile housing design
-  IP65 grade protection
-  5 Years warranty
-  Energy efficiency class A+ & A++

## TECHNICAL DATA

### Electrical data

Rated power	150 W
Operating voltage	AC100~277V
Operating frequency	50~60Hz
Power factor	>0.95

### Photometrical data

Color temperature	2700K - 6500K
Luminous flux (lm)	21000±1500
Color rendering index Ra	>80

### Light Technical Data

Beam angle	90°
------------	-----

### Dimensions

Height (mm)	190
Diameter (mm)	320

### Temperature & operating conditions

Ambient Temperature	-30~+55°C
---------------------	-----------

### General information

Mounting type	Surface mounted
LED type	SMD LED
Lifespan	50000 hours



SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
CLXHB O9-150 W	140±10lm/W	150 W	65	YES

**TECHNICAL DRAWING**

