



AREAS OF APPLICATION

- 💡 Parking Lots
- 💡 Gas stations and Storage areas.
- 💡 Other applications subject to harsh, wet or otherwise challenging conditions

PRODUCT BENEFITS

- 💡 The massive internal aluminum housing provides excellent heat dissipation.
- 💡 Simple and Flexible installation
- 💡 The polycarbonate housing is cast from a single mold and therefore absolutely dust and water proof with an IP66 rating.
- 💡 UV Stabilised prismatic diffuser for uniform light distribution and high efficiency.
- 💡 High quality LED driver, flicker free driver and Stainless steel surface mounting clamps.

PRODUCT FEATURES

- 💡 Type of protection : IP66
- 💡 5 Years Warranty.
- 💡 Both standalone and continuous mounting are available
- 💡 Energy efficiency class : A+ & A++

TECHNICAL DATA

Electrical data

Rated power	60W
Operating voltage	AC100-277V
Operating frequency	50/60Hz
Power factor	0.90

Photometrical data

Color temperature	2700-6500K
Luminous flux	7800±600lm
Color rendering index Ra	>80

Light Technical Data

Beam angle	120°
------------	------

Dimensions

Length	1600mm
Width	72mm

Temperature & operating conditions

Ambient Temperature	-30~+50°C
---------------------	-----------

General information

Mounting type	Surface
LED type	CREE LED
Lifespan	50,000h



SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
CLX T55-60W15	130±10lm/W	60W	66	NO

TECHNICAL DRAWING

