



## AREAS OF APPLICATION

- Parking Facilities, Corridors and halls
- Warehouses and other storage areas
- Factories and production areas.

## PRODUCT BENEFITS

- The massive internal aluminum housing provides excellent heat dissipation.
- Its polycarbonate housing is cast from a single mold
- The internal aluminum core deals with the heat from the LED chips and assures a long lifespan
- Slim design, ideal for space-constrained industrial applications
- The LED Tri-Proof Lights uses powerful SMD2835 Chip sets for achieving the highest efficiency in lighting

## PRODUCT FEATURES

- Type of protection IP65
- 5 Years Warranty.
- Energy efficiency class:A+
- No UV or IR and completely mercury free

## TECHNICAL DATA

### Electrical data

Rated power	40W
Operating voltage	AC100-277V
Operating frequency	50~60Hz
Power factor	0.90

### Photometrical data

Color temperature	2700-6500K
Luminous flux	5200±400lm
Color rendering index Ra	>80

### Light Technical Data

Beam angle	120°
------------	------

### Dimensions

Length	615mm
Width	75mm

### Temperature & operating conditions

Ambient Temperature	-30°~ +50°C
---------------------	-------------

### General information

Mounting type	Surface
LED type	SMD LED
Lifespan	50,000h



SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
CLXT57-40W06	130±10m/W	40W	65	YES

**TECHNICAL DRAWING**

