







## AREAS OF APPLICATION

-  General indoor illumination
-  Architectural lighting
-  Facade accent lighting

## PRODUCT BENEFITS

-  Highest quality components and premium packaged 2835 LEDs
-  Easy mounting on many smooth surfaces thanks to self-adhesive tape at the back
-  High-performance silicone for extremely long life and flexibility
-  Direct connection to AC power supply thanks to integrated control gear
-  SMD2835, Single Row led strip light with Push-inconnectors enable automatic wiring

## PRODUCT FEATURES

-  Type of protection: IP68
-  Material:Silicon Glue with UV/IR protected
-  Type of LED:SMD 2835,60LED/m

## TECHNICAL DATA

### Electrical data

Rated power	25W/m
Operating voltage	DC 12V
Operating frequency	-
Power factor	0.90

### Photometrical data

Color temperature	2700-6500K
Luminous flux	1320lm/m
Color rendering index Ra	>80

### Light Technical Data

Beam angle	120°
------------	------

### Dimensions

Length	5000mm
Width	10mm

### Temperature & operating conditions

Ambient Temperature	-15°~ +60°
---------------------	------------

### General information

Colour consistency	≤ 3 SDCM
LED type	LED SMD
Lifespan	25,000h



SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
2835-240P	92lm/W	25W/m	68	NO

**TECHNICAL DRAWING**

