






AREAS OF APPLICATION

-  Landscape Area
-  Outdoor Pathway
-  Garden

PRODUCT BENEFITS

-  Matching colour temperature and finish to the Architectural exterior range
-  Die-cast aluminium construction with Stainless steel front and Clear toughened glass
-  Good glare reduction and low maintenance and operation costs, CREE Led's.
-  Suitable for use in areas with Garden and Outdoor Pathways
-  Excellent diffused beam shape from a range of optics

PRODUCT FEATURES

-  Type of protection IP66
-  3 Years Warranty
-  Colour Rendering Index R:80

TECHNICAL DATA

Electrical data

Rated power	40W
Operating voltage	DC24V/AC 220-240V
Operating frequency	50-60Hz
Power factor	0.90

Photometrical data

Color temperature	RGBW/WW
Luminous flux(lm)	2800lm
Color rendering index Ra	80

Light Technical Data

Beam angle	10°, 30°, 45°, 60°
------------	--------------------

Dimensions

Diameter (mm)	Ø200mm
Height (mm)	181mm

temperature & operating conditions

Ambient Temperature	-25°C...+50°C
---------------------	---------------

General information

Mounting type	Spike Mounted
LED type	CREE LED
Lifespan	50,000h

SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
CLX WN-FL01-RGB	70lm/W	40W	66	NO

● TECHNICAL DRAWING

