



## AREAS OF APPLICATION

- Residential roads and streets
- Loading areas and sporting venues.
- Parks and parking lots

## PRODUCT BENEFITS

- Highly efficient SMD LED chip and high IP rating on luminaire front side
- Highly reliability and high performance LED light source with CREE LED Chip and has excellent light distribution.
- Durable and long-lasting power driver with flicker free
- Aluminum PCB with a Thermal Conductivity rating with 5W EMC5050 chips

## PRODUCT FEATURES

- Extremely energy efficient up to 140 lm/W and IP66 for all weather conditions
- Energy efficiency class:A++
- 5 Years warranty

## TECHNICAL DATA

### Electrical data

Rated power	30W
Operating voltage	AC100~277V
Operating frequency	50~60Hz
Power factor	>0.9

### Photometrical data

Color temperature	2700-6500K
Luminous flux (lm)	4200±300
Color rendering index Ra	>80

### Light Technical Data

Beam angle	T2-S ,T3-M
------------	------------

### Dimensions

Length (mm)	508
Width (mm)	180

### Temperature & operating conditions

Ambient Temperature	-20°~+65°C
---------------------	------------

### General information

Mounting type	Surface mounted
LED type	SMD LED
Lifespan	5 Years



SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
CLX T68-30W	140±10lm/W	30W	66	YES

**TECHNICAL DRAWING**

